



PTAC Made Simple



Traditional experience, premium comfort

With **Distinctions** PTAC units, you have a reliable and high-quality option—while your guests enjoy ideal comfort.



Model	DCP 073A25AA	DCP 073A35AA	DCP 093A25AA	DCP 093A35AA	DCP 093A50AA	DCP 123A25AA	DCP 093A35AA	DCP 123A50AA	DCP 153A50AA	DCP 153A35AA
Cooling										
Voltage	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230
Capacity (BTU/h)	7,200 / 7,000	7,200 / 7,000	9,200 / 9,000	9,200 / 9,000	9,200 / 9,000	12,000 / 11,800	12,000 / 11,800	12,000 / 11,800	14,700 / 14,500	14,700 / 14,500
Amps	2.45 / 2.60	2.45 / 2.60	3.54 / 3.83	3.54 / 3.83	3.54 / 3.83	4.9 / 5.3	4.9 / 5.3	4.9 / 5.3	6.03 / 6.58	6.03 / 6.58
Watts	550 / 535	550 / 535	814 / 796	814 / 796	814 / 796	1,121 / 1,102	1,121 / 1,102	1,121 / 1,102	1,390 / 1,370	1,390 / 1,370
EER	13.1	13.1	11.3	11.3	11.3	10.7	10.7	10.7	10.6	10.6
CFM (cool/wet coil)	high	334	334	435	435	435	384	384	384	376
	low	236	236	341	341	341	311	311	311	315
CFM (dry)	high	334	334	435	435	435	384	384	384	376
	low	237	237	341	341	341	311	311	311	315
Universal										
Vent door CFM	61.1 / 57.6 / 50.6	61.1 / 57.6 / 50.6	61.1 / 57.6 / 50.6	61.1 / 57.6 / 50.6	61.1 / 57.6 / 50.6	62 / 60 / 56	62 / 60 / 56	62 / 60 / 56	62 / 60 / 56	62 / 60 / 56
Dehumidification (pints/hr.)	0.63	0.63	1.18	1.18	1.18	2.75	2.75	2.75	4.55	4.55
Net weight (lbs.)	101.63	101.63	98.1	98.1	98.1	108.69	108.69	108.69	113.1	113.1
Ship weight (lbs.)	112.43	112.43	108.69	108.69	108.69	119.49	119.49	119.49	122.8	122.8
CFM (dry)	334	334	435	435		384	384	384	376	376
Electric Heat										
Voltage	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230
Heater size (kW)	2.5	3.5	2.5	3.5	5	2.5	3.5	5	5	3.5
Heating capacity (BTU/h)	7,800 / 6,300	10,900 / 8,900	7,800 / 6,300	10,900 / 8,900	15,000 / 12,200	7,800 / 6,300	10,900 / 8,900	15,000 / 12,200	15,000 / 12,200	10,900 / 8,900
Watts	2,535 / 2,080	3,519 / 2,850	2,535 / 2,080	3,535.5 / 2,897	4,769 / 3,953	2,535 / 2,080	3,535 / 2,900	4,769 / 3,953	4,769 / 3,953	3,535 / 2,900
Amps	10.8 / 9.8	15.30 / 13.70	10.8 / 9.8	15.3 / 13.7	22 / 19.7	10.8 / 9.8	15.3 / 13.7	22 / 19.7	22 / 19.7	15.3 / 13.7



Model	DHP 093A25AA	DHP 093A35AA	DHP 093A50AA	DHP 123A25AA	DHP 123A35AA	DHP 123A50AA	DHP 153A35AA	DHP 153A50AA	DHP 094A35AA	DHP 124A35AA	
Cooling											
Voltage	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	265	265	
Capacity (BTU/h)	9,000 / 8,800	9,000 / 8,800	9,000 / 8,800	12,000 / 11,800	12,000 / 11,800	12,000 / 11,800	14,700 / 14,500	14,700 / 14,500	9,000	12,000	
Amps	3.46 / 3.75	3.46 / 3.75	3.46 / 3.75	5.0 / 5.4	5.0 / 5.4	5.0 / 5.4	6.03 / 6.58	6.03 / 6.58	3.01	4.31	
Watts	796 / 778	796 / 778	796 / 778	1,142 / 1,124	1,142 / 1,124	1,142 / 1,124	1,390 / 1,370	1,390 / 1,370	796	1,142	
EER	11.4	11.4	11.4	10.5	10.5	10.5	10.6	10.6	11.3	10.5	
CFM (cool/wet coil)	high	431	431	431	387	387	387	374	374	388	379
	low	333	333	333	309	309	309	312	312	321	313
CFM (dry)	high	431	431	431	387	387	387	374	374	388	380
	low	333	333	333	309	309	309	312	312	322	314
Universal											
Vent door CFM	61.1 / 57.6 / 50.6	61.1 / 57.6 / 50.6	61.1 / 57.6 / 50.6	62 / 60 / 56	62 / 60 / 56	62 / 60 / 56	62 / 60 / 56	62 / 60 / 56	61.1 / 57.6 / 50.6	62 / 60 / 56	
Dehumidification (pints/hr.)	1.06	1.06	1.06	2.81	2.81	2.81	4.29	4.29	1.06	2.81	
Net weight (lbs.)	102.51	102.51	102.51	115.96	115.96	115.96	116.84	116.84	101.19	113.1	
Ship weight (lbs.)	112.88	112.88	112.88	125.44	125.44	125.44	126.54	126.54	111.99	126.76	
Electric Heat											
Voltage	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	265	265	
Heater size (kW)	2.5	3.5	5	2.5	3.5	5	3.5	5	3.5	3.5	
Heating capacity (BTU/h)	7,800 / 6,300	10,900 / 8,900	15,000 / 12,200	7,800 / 6,300	10,900 / 8,900	15,000 / 12,200	10,900 / 8,900	15,000 / 12,200	10,900	10,900	
Watts	2,535 / 2,080	3,535.5 / 2,897	4,769 / 3,953	2,535 / 2,080	3,535 / 2,900	4,769 / 3,953	3,535 / 2,900	4,769 / 3,953	3,500	3,500	
Amps	10.8 / 9.8	15.3 / 13.7	22 / 19.7	10.8 / 9.8	15.3 / 13.7	22 / 19.7	15.3 / 13.7	22 / 19.7	13.46	13.46	
Reverse Cycle											
Voltage	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	208 / 230	265	265	
Capacity (BTU/h)	8,100 / 7,900	8,100 / 7,900	8,100 / 7,900	10,800 / 10,500	10,800 / 10,500	10,800 / 10,500	13,500 / 13,200	13,500 / 13,200	8,100	10,800	
Amps	3.04 / 3.28	3.04 / 3.28	3.04 / 3.28	4.3 / 4.6	4.3 / 4.6	4.3 / 4.6	5.38 / 5.82	5.38 / 5.82	3.1	4.3	
Watts	700 / 680	700 / 680	700 / 680	990 / 963	990 / 963	990 / 963	1,237 / 1,209	1,237 / 1,209	719	989	
COP	3.40	3.40	3.40	3.2	3.2	3.2	3.20	3.20	3.3	3.2	
CFM (dry)	431	431	431	387	387	387	374	374	388	380	